

Thoelen Pump Selections

Model	Flow/Min (Min to Max)	Tubing Sizes Wall x ID	Motor Specs	Overall Dimension Height x Width x Depth
TP S-50	.10 ml / 40.0 ml	<ul style="list-style-type: none"> • 1mm x 1mm • 1mm x 2mm • 1mm x 3mm 	<ul style="list-style-type: none"> • 12VDC Geared Motor • Range of 6 to 12 VDC • 200 mA consumption 	<ul style="list-style-type: none"> • 50.4 x 39.2 x 79.8 • 2" x 1.54" x 3.14"
TP 2004	6.3 ml / 57 ml	• 3.2mm • 4.0mm	• Geared DC or AC	<ul style="list-style-type: none"> • 78.7 x 58.0 x 75.2 • 3.1" x 2.3" x 3"
TP 3005	86 ml / 812 ml	<ul style="list-style-type: none"> • 3.2mm x 1.6mm • 4.8mm x 1.6mm 	<ul style="list-style-type: none"> • Geared AC or DC • 12 or 24 VDC • AC Shaded Pole Motor 	<p>Pump Head Only Dim.</p> <ul style="list-style-type: none"> • 86.1 x 66.5 x 34.6 • 3.4" x 2.6" x 1.36"
TP 4000	410 ml / 3,833 ml	<ul style="list-style-type: none"> • 6.4mm x 2.4mm • 8.0mm x 2.4mm 	<ul style="list-style-type: none"> • Geared AC or DC • 12 or 24 VDC • Shaded Pole AC 	<p>Dimension with 24VDC Motor</p> <ul style="list-style-type: none"> • 117.4 x 116 x 149.3 • 4.62" x 4.6" x 5.9"

Randolph Austin Company

Toll-free in US 800-531-5262 | 512-282-1590

sales@randolphaustin.com